

# Xerox® DocuMate® 4799 Scanner

## Extra Performance and Versatility for Heavy Scanning Demands

### Features:

- 112 ppm / 224 ipm\* at 300 dpi
- A3 (11" x 17") paper size
- ADF holds 350 pages†
- 3 Ultrasonic double feed detection sensors
- Create searchable PDF files to make it easy to find scanned documents
- Pre- & Post-Scan Imprinter (sold separately)
- Colour Space Compatibility with Xerox® iGen® digital press
- Xerox® FreeFlow Makeready® application Supported

\* Landscape A4, b&w, gray & Colour.

† 20 lb., 75-80 g/m<sup>2</sup> paper



Document Manager Magazine's  
2015 Product of the Year, and  
2016 High Volume Imaging  
Product of the Year.

### OVERCOME YOUR FEAR OF DIFFICULT DOCUMENTS

Versatility, high-speed and superior reliability make the Xerox® DocuMate® 4799 a powerful scanner for demanding environments. With up to a 40,000 page per day duty cycle, this innovative workhorse scans up to 112 pages per minute and employs three advanced sensor systems: ultrasonic double feed detection, stapled document detection and intelligent feed control to ensure that your scan job will not get interrupted.

Documents of various sizes can be stacked together in the automatic feed tray without worry because the Xerox® DocuMate® 4799 employs not one, but three ultrasonic double feed detection sensors to cover the entire width of a document. The scanner has another set of sensors designed to detect staples anywhere in a document. As soon as a staple is detected, the scanning process is halted—minimizing damage to the optical glass and your documents. A third set of sensors constantly monitors the thickness of documents being fed into the scanner and automatically adjusts the roller pressure to ensure that all pages are accurately fed. This combination of sensors creates one of the most reliable feed mechanisms available today.

Up to 350 mix-sized documents can be stacked in the center of the automatic feeder. There is no need to organize documents according to their size, so scanning is fast, easy and efficient. A

pre- and post-scan imprinter is also available for the Xerox® DocuMate® 4799 and is supported through the included TWAIN™ and ISIS® drivers.

### ADVANCED IMAGE PROCESSING TECHNOLOGY

The Xerox® DocuMate® 4799 provides both high quality image enhancement and increased productivity with Kofax® VRS™ Professional AIPE-EBC for auto-everything scanning, including Auto Rotation, Blank Page Deletion and Auto Colour Detect. VRS Professional improves your workflow and reduces the total time needed to scan even the largest volumes of mixed batch documents. Taken together, the Xerox® DocuMate® 4799 and the Kofax VRS Professional bundle translate into real and measurable savings—fewer manual steps, reduced storage requirements and less operator intervention.

When the occasional paper jam happens, the Xerox® DocuMate® 4799 is very easy to maintain. Its unique “clamshell” design allows full access to the entire paper path, so you can clear paper jams or clean the unit without calling a service technician. The rollers are easy to replace, improving the unit’s cost effectiveness, and have a long service life.

Designed for document capture and workflow the Xerox® DocuMate® 4799 is everything you ever wanted in a high-speed document scanner: productivity, reliability and innovation.

# Xerox® DocuMate® 4799 Scanner Software Solutions

## IMAGE ENHANCEMENT TECHNOLOGY

Visioneer® OneTouch® is integrated with image enhancing software such as Visioneer Acuity with DriverPLUS or Kofax® VRS™ (VirtualReScan), model dependent. Using advanced algorithms and dynamic thresholding, these software tools effectively improve the visual clarity of every document that you scan, applying intelligent correction to imperfect images, increasing OCR accuracy, and saving time.

## NUANCE® SEARCHABLE PDF SOLUTION

Nuance OmniPage® and PDF Converter provide everything you need to create, convert, edit, assemble and securely share searchable PDF files with precision OCR analysis, advanced layout detection and Logical Form Recognition™ (LFR) technology. Combining powerful functionality, superior Microsoft® Office® support and DMS integration into one package.

## OFFICE GEMINI DOKMEE CAPTURE

Dokmee Capture production scanning software provides all the features required for document capture, processing and reporting. It allows businesses both large and small to easily convert their scanned documents into digital files, capture images and information contained in them, and then organize it all into searchable data. This mission-critical business information is then placed into a centralized location to be easily searched, stored and retrieved when needed.

Xerox® DocuMate® 4799 Product Specifications		
Model Number w/VRS Pro (Euro/UK)	XDM47995E-WU	100N02782
Model Number w/VRS Basic (Euro/UK)	XDM47995E-VRS/B	100N02825
Scan Speed	112 ppm / 224 ipm (Colour, greyscale, or b&w @ 150, 200, or 300 dpi, landscape A4)	
Scan Method	Automatic Document Feeder (ADF)	
Imaging Sensor	Dual Colour CIS detector	
Light Source	Xenon Lamp	
Background	Switchable black or white background	
Optical Resolution	600 dpi	
Output Bit Depth	24-bit Colour, 8-bit greyscale, 1-bit black & white	
Other Functions	Length control, barcode detection, patch code detection, Automatic separation, control sheet, long paper mode	
Interface	Hi-speed USB 2.0 (1.1 compatible)	
Detection	Ultrasonic double feed detection (3 positions), stapled document detection	
Accessories	DocuMate 4700 flatbed scanner, Pre- & Post-Scan Imprinter	
ADF Minimum Document Size	48 x 70 mm (1.9" x 2.8")	
ADF Maximum Document Size	302 x 432 mm (11.9" x 17"); custom lengths up to 2540 mm (100")	
ADF Capacity	Up to 350 sheets (20 lb., 75-80 g/m <sup>2</sup> paper)	
Document Weight	Thin mode: 5 - 13 lbs. (20 - 50 g/m <sup>2</sup> )	
	Normal mode: 13 - 42 lbs. (50 - 157 g/m <sup>2</sup> )	
	Thick mode: 42 - 56 lbs. (157 - 209 g/m <sup>2</sup> )	
	Auto mode: 5 - 42 lbs. (20 - 157 g/m <sup>2</sup> )	
Document Thickness	1.9 - 7.9 mils (0.04 - 0.2 mm) Straight path: max. 23.6 mils (0.6 mm) Note: 1 mil = 0.001"	
Duty Cycle	40,000 pages/day	
Power Requirement	AC 100 – 240 V, 50/60 Hz	
Power Consumption	150 watts while scanning	
	70 watts on standby	
	5.3 watts or less in Sleep Mode	
Operating Environment	Temperature: 59°F - 86°F (15°C - 30°C), Humidity: 10 - 80 % RH	
Storage Environment	Temperature: 32°F - 104°F (0°C - 40°C), Humidity: 30 - 80 % RH	
Dimensions	474 x 585 x 329 mm (18.7" x 23" x 13")	
Weight	25 kg (55 lbs.)	

For more information about the Xerox line of scanners, visit [www.xeroxscanners.com](http://www.xeroxscanners.com)



©2018 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, DocuMate®, FreeFlow Makeready® and iGen® are registered trademarks of Xerox Corporation in the United States and other countries, and are used under license from Xerox Corporation. Visioneer® is an authorized trademark licensee of Xerox®, Visioneer® and Visioneer OneTouch® are trademarks of Visioneer, Inc. Kofax®, VirtualReScan® and VRS™ are trademarks of Kofax, Inc. Nuance® and OmniPage® are trademarks of Nuance Communications, Inc. or its affiliates in the United States and/or other countries. Dokmee Capture® is a registered trademark of Office Gemini. Microsoft®, Windows Vista®, Windows® and XP® are trademarks of Microsoft Corporation in the United States and/or other countries. Intel® and Pentium® are trademarks of Intel Corporation in the U.S. and/or other countries. TWAIN™ is a trademark of TWAIN Working Group. EMC®, Captiva®, and ISIS® are trademarks of EMC Corporation. ENERGY STAR® and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. Universal Serial Bus is a trademark of USB Implementers Forum, Inc. (USB-IF). All other trademarks are the property of their respective owners and are hereby acknowledged. Prices, features, specifications, capabilities, appearance and availability of Xerox® products and services are subject to change without notice. 02/18 BR23968-UK

## BOX CONTENTS

- DocuMate 4799 Scanner
- Quick Installation Guide
- Technical Support Card
- Blower w/Brush
- Roller Cleaning Paper, Cleaning Paper Card
- Shading Sheet, Shading Caution Leaflet
- DFP (Double Feed Protection) Roller
- AC Power Cord US (1), Euro/UK (2)
- USB Cable
- DVD-ROM including:
  - User's Manual
  - Kofax VRS Pro (with AIPE-EBC) or with VRS Basic depending on SKU\*
  - Nuance® OmniPage® Pro
  - Nuance PDF Converter
  - Office Gemini Dokmee Capture
  - Visioneer OneTouch
  - Visioneer Acuity
  - Scanner Drivers: DriverPLUS TWAIN™, Microsoft Windows® Image Acquisition (WIA), EMC Captiva ISIS®

## PC MINIMUM SYSTEM REQUIREMENTS

- Intel® Pentium® 4 or equivalent processor
- Compatible with:
  - Windows® 10 Pro, Home, Enterprise and Education
  - Windows 7 Pro, Home, Enterprise and Ultimate
  - Windows 8/8.1 Pro, Core and Enterprise
  - Windows Vista® Home Basic, Home Premium, Business, Enterprise, Ultimate, Starter
  - Windows XP® Home, Professional
- 350 MB available hard disk space
- DVD-ROM drive
- USB port

## WARRANTY INFORMATION

- 90-Day Advance Exchange Warranty
- Optional 1-5 year Advance Exchange
- Optional 1-5 year Next Day Business\*\*
- Optional 1-5 year 4-hour response\*\*

## CONSUMABLES:

- 4799ROLL-KIT - User installable roller assembly. Roller kits last up to 400,000 scans, depending on scanning conditions.

\*\*Includes 1 preventive maintenance visit per year. Coverage is available Monday – Friday 8:00 am to 5:00 pm (local time), excluding US holidays.

\*\*\* Dokmee Capture is not supported on Microsoft Windows XP  
 ¥ Kofax VRS 4.5 is not supported on Microsoft Windows 8

